

MANCONI 250 JB JOLLY



Installation area	448 x 359 mm
Working area	555 x 487 x 421 mm
Blade diameter	250 mm
Blade speed	280 rpm (belt)
Slice thickness	0 to 16 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	24 kg
Carriage travel	245 mm
Electrical specifications	230-230V 50 Hz/220W a.c. monophase
Cutting capacity	Ø 180 mm - ▧ 215 x 154 mm

MANCONI 250 VK VE



Overall dimensions	573 x 533 x 444 mm
Installation area	418 x 342 mm
Working area	590 x 533 x 444 mm
Blade diameter	250 mm
Blade speed	200 rpm
Slice thickness	0 to 24 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	28,5 kg
Carriage travel	250 mm
Electrical specifications	220-230V / 340W a.c. monophase; 220-230V / 380-400V /230W a.c. threephase
Cutting capacity	Ø 170 mm - ▧ 207 x 155 mm

MANCONI 300IB DOC



Overall dimensions	655 x 539 x 456 mm
Installation area	532 x 441 mm
Working area	746 x 539 x 456 mm
Blade diameter	300 mm
Blade speed	250 rpm (belt)
Slice thickness	0 to 16 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	30 kg
Carriage travel	315 mm
Electrical specifications	220-230V / 370W a.c. monophase; 220-230V / 380-400V /230W a.c. threephase
Cutting capacity	Ø 220 mm - ▧ 283 x 200 mm

MANCONI 300 VK VE



Overall dimensions	680 x 597 x 515 mm
Installation area	521 x 418 mm
Working area	680 x 597 x 515 mm
Blade diameter	300 mm
Blade speed	200 rpm
Slice thickness	0 to 24 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	43 kg
Carriage travel	300 mm
Electrical specifications	220-230V / 340W a.c. monophase; 220-230V / 380-400V /230W a.c. threephase; 120V / 60Hz / 340W a.c. monophase
Cutting capacity	Ø 210 mm - ▧ 250 x 190 mm

Pro více informací nás kontaktujte.

Dále nabízíme také: 250 IK, 300 IK, 300 VK BV, 330 IK, 330 IK SA