

# OVERVIEW OF MODELS



MULTIMAX 6-11

<b>ELECTRIC</b>	Art.-Nr. EL6103008-2A
<b>GAS</b>	Art.-Nr. EL6106005-2A

<b>ELECTRIC</b>	
Connected load	11 kW
Voltage	400 V 3N AC
Protection	3 x 16 Amp
Weight	122 kg
W/D/H	925/805/840 mm

<b>GAS</b>	
Connected load	12 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	132 kg
W/D/H	925/805/840 mm

**OPTIONS (EXAMPLES)**

Right-hinged	
with AC (E)	Art.-Nr. EL6103004-2A
with AC (G)	Art.-Nr. EL6106003-2A
with Multi-Eco-System (E)	Art.-Nr. EL6103006-2A
with Multi-Eco-System + AC (E)	Art.-Nr. EL6103001-2A
Left-hinged (E)	
with AC (E)	Art.-Nr. EL6103005-2A
with Multi-Eco-System (E)	Art.-Nr. EL6103007-2A
with Multi-Eco-System + AC (E)	Art.-Nr. EL6103002-2A



MULTIMAX 10-11

<b>ELECTRIC</b>	Art.-Nr. EL1103008-2A
<b>GAS</b>	Art.-Nr. EL1106005-2A

<b>ELECTRIC</b>	
Connected load	17 kW
Voltage	400 V 3N AC
Protection	3 x 25 Amp
Weight	156 kg
W/D/H	925/805/1120 mm

<b>GAS</b>	
Connected load	20 kW
Voltage	230 V 1N AC
Protection	3 x 16 Amp
Weight	166 kg
W/D/H	925/805/1120 mm

**OPTIONS (EXAMPLES)**

Right-hinged	
with AC (E)	Art.-Nr. EL1103004-2A
with AC (G)	Art.-Nr. EL1106003-2A
with Multi-Eco-System (E)	Art.-Nr. EL1103006-2A
with Multi-Eco-System + AC (E)	Art.-Nr. EL1103001-2A
Left-hinged (E)	
with AC (E)	Art.-Nr. EL1103005-2A
with Multi-Eco-System (E)	Art.-Nr. EL1103007-2A
with Multi-Eco-System + AC (E)	Art.-Nr. EL1103002-2A



MULTIMAX 20-11

<b>ELECTRIC</b>	Art.-Nr. EL2103004-2X
<b>GAS</b>	Art.-Nr. EL2106004-2X

<b>ELECTRIC</b>	
Connected load	45 kW (34 kW)
Voltage	400 V 3N AC
Protection	3 x 80 Amp (3 x 63 Amp)
Weight	295 kg
W/D/H	1030/880/1930 mm

<b>GAS</b>	
Connected load	40 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	320 kg
W/D/H	1030/880/1930 mm

**OPTIONS (EXAMPLES)**

Right-hinged	
with AC (E)	Art.-Nr. EL2103002-2X
with AC (G)	Art.-Nr. EL2106002-2X
with Multi-Eco-System (E)	Art.-Nr. EL2103003-2X
with Multi-Eco-System + AC (E)	Art.-Nr. EL2103001-2X

1 mobile tray rack GN 1/1 in series



MULTIMAX 20-21

<b>ELECTRIC</b>	Art.-Nr. EL2203005-2X
<b>GAS</b>	Art.-Nr. EL2206005-2X

<b>ELECTRIC</b>	
Connected load	68 kW (52 kW)
Voltage	400 V 3N AC
Protection	3 x 100 Amp (3 x 80 Amp)
Weight	495 kg
W/D/H	1310/1086/1925 mm

<b>GAS</b>	
Connected load	70 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	530 kg
W/D/H	1310/1086/1925 mm

**OPTIONS (EXAMPLES)**

Right-hinged	
with AC (E)	Art.-Nr. EL2203003-2X
with AC (G)	Art.-Nr. EL2206003-2X
with Multi-Eco-System (E)	Art.-Nr. EL2203004-2X
with Multi-Eco-System + AC (E)	Art.-Nr. EL2203001-2X

1 mobile tray rack GN 2/1 in series

