

### MANCONI 350 IK DUAL



Installation area	577 x 463 mm
Working area	800 x 577 x 506 mm
Blade diameter	350 mm
Blade speed	230 rpm (belt)
Blade speed	200 rpm (gear)
Slice thickness	0 to 24 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	45,4 kg
Carriage travel	361 mm
Electrical specifications	220-230V / 290W a.c. monophase; 220-230V / 380-400V / 350W a.c. threephase; 120V / 60Hz / 350W a.c. monophase
Cutting capacity	Ø 252 mm - 300 x 225 mm

### MANCONI 350 VK TC DUAL



Installation area	510 x 510 mm
Working area	816 x 730 x 559 mm
Blade diameter	350 mm
Blade speed	230 rpm (belt)
Blade speed	200 rpm (gear)
Slice thickness	0 to 24 mm
Carriage travel	370 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	53,5 kg
Electrical specifications	220-230V / 290W a.c. monophase; 220-230V / 380-400V / 350W a.c. threephase
Cutting capacity	Ø 252 mm - 335 x 252 mm

### MANCONI 350 VK BV DUAL



Installation area	510 x 510 mm
Working area	845 x 686 x 559 mm
Blade diameter	350 mm
Blade speed	230 rpm (belt)
Blade speed	200 rpm (gear)
Slice thickness	0 to 24 mm
Carriage travel	370 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	53,2 kg
Electrical specifications	220-230V / 290W a.c. monophase; 220-230V / 380-400V / 350W a.c. threephase
Cutting capacity	Ø 252 mm - 320 x 252 mm

Pro více informací nás kontaktujte

Dále nabízíme také typy: 370 IK DUAL, 370 VK TC DUAL, 370 VK BV DUAL, 370 VK TC DUAL BIG, 370 VK BV DUAL BIG