

## MANCONI 250 IX



Overall dimensions	530 x 445 x 430 mm
Installation area	443 x 342 mm
Blade diameter	250 mm
Blade speed	286 g/min
Slice thickness	0 to 16 mm
Carriage travel	245 mm
Electrical protection	IPX3
Net weight	20 kg
Electrical specifications	230-230V 50 Hz/210W a.c. monophase; 220-230V, 380-400V / 270W a.c. threephase; 120 V 60 Hz/210W a.c. monophase
Cutting capacity	Ø 180 mm - $\nabla$ 215 x 165 mm

## MANCONI 250 VX VE



Overall dimensions	530 x 508 x 450 mm
Installation area	443 x 342 mm
Blade diameter	250 mm
Blade speed	286 g/min
Slice thickness	0 to 16 mm
Carriage travel	245 mm
Electrical protection	IPX3
Net weight	20 kg
Electrical specifications	230-230V 50 Hz/210W a.c. monophase; 220-230V, 380-400V / 270W a.c. threephase; 120 V 60 Hz/210W a.c. monophase
Cutting capacity	Ø 180 mm - $\nabla$ 215 x 165 mm

## MANCONI 300 IX



Overall dimensions	609 x 509 x 481 mm
Installation area	501 x 409 mm
Blade diameter	300 mm
Blade speed	250 rpm
Slice thickness	0 to 16 mm
Carriage travel	297 mm
Electrical protection	IPX3
Net weight	26,5 kg
Electrical specifications	230-230V 50 Hz/242W a.c. monophase; 220-230V, 380-400V / 350W a.c. threephase; 120 V 60 Hz/242W a.c. monophase
Cutting capacity	Ø 220 mm - $\nabla$ 255 x 220 mm

## MANCONI 300 VX VE



Overall dimensions	610 x 547 x 492 mm
Installation area	501 x 389 mm
Blade diameter	300 mm
Blade speed	250 rpm
Slice thickness	0 to 16 mm
Carriage travel	297 mm
Electrical protection	IPX3
Net weight	27,2 kg
Electrical specifications	230-230V 50 Hz/242W a.c. monophase; 220-230V, 380-400V / 350W a.c. threephase; 120 V 60 Hz/242W a.c. monophase
Cutting capacity	Ø 220 mm - $\nabla$ 255 x 220 mm

Pro více informací nás kontaktujte

Dále nabízíme také typy: 300 VX BV, 350 IX, 350 VK TC, 350 VK BV