

## S.A.M. 300



Application range	Slicing of fine meat and cheese products
Area of use	commercial, industrial
Temperature range	+5°C to +35°C
Option	Cheese version, Packer T
<b>Available in 3 carriage versions:</b>	
<b>Carriage 250 W x L:</b>	220 mm x 250 mm
Max. product feed	120 mm
Max. product size	Ø 180 or 210 x 150 mm
<b>Carriage 350 W x L:</b>	220 mm x 350 mm
Max. product feed	220 mm
Max. product size	Ø 180 or 210 x 150 mm
<b>Carriage XXL W x L:</b>	275 mm x 350 mm
Max. product feed	220 mm
Max. product size	Ø 180 or 270 x 150 mm
<b>Weight and dimensions</b>	
Net weight	37 kg
Dimensions LxWxH	475/575 x 630 x 405 mm
<b>Mechanical data</b>	
Knife diameter	Ø 300 mm
Product holder W x L	see above
Max. product feed drive	see above
Max. product size W x H	see above
Slice thickness	0,5 - 12mm
<b>Electrical data</b>	
Supply voltage/frequency	230V/50Hz, 3x400V/50Hz
Current consumption 1~/3~	1,35A / 0,55A
Power outlet fuse	min. 10A
<b>Other data</b>	
Noise level	- 55 dB(A)

## S.A.M. 308 F



Application range	Slicing of fine meat and cheese products
Area of use	commercial, industrial
Temperature range	+5°C to +35°C
Option	Cheese version (non-stick coating, special cheese transport system), motor-powered conveyor belt (FB), can be operated in both directions
<b>Weight and dimensions</b>	
Net weight	83 kg / FB: 91 kg
Dimensions LxWxH	925 x 600 x 630 mm
<b>Mechanical data</b>	
Knife diameter	Ø 300 mm
Product holder W x L	240 mm x 500 mm
Max. product feed drive	400 mm
Max. product size W x H	Ø 150 or 210 x 140 mm
Slice thickness	0,5 - 7mm
Slicing speed	up to 55 strokes/min.
<b>Electrical data</b>	
Supply voltage/frequency	230V/50Hz, 3x400V/50Hz
Current consumption 1~/3~	2,34A / 1,54A
Power outlet fuse	min. 10A
<b>Other data</b>	
Noise level	< 70 dB(A)

Nabízíme i další typy nářezových strojů S.A.M.

Pro více informací nás kontaktujte.

[www.gastrotechnogroup.cz](http://www.gastrotechnogroup.cz)